

Temporal Trends of Environmental Contaminants in a Durham, NC, Creek Using Non-Targeted Analysis

Imari Walker-Franklin, Julia Apoian, Nateja Hale, Cana Gerald, Porché L. Spence, Omar Christian, and Carresse Gerald



RTI Press publication RR-0056-2604

RTI International is an independent scientific research institute dedicated to improving the human condition. The RTI Press mission is to disseminate information about RTI research, analytic tools, and technical expertise to a global audience. RTI Press publications are peer-reviewed by at least two independent substantive experts and one or more Press editors.

Suggested Citation

Walker-Franklin, I., Apoian, J., Hale, N., Gerald, C., Spence, P. L., Christian, O., and Gerald, C. (2026). *Temporal trends of environmental contaminants in a Durham, NC, creek using non-targeted analysis*. RTI Press Publication No. RR-0056-2604. RTI Press. <https://doi.org/10.3768/rtipress.2026.rr.0056.2604>

Cover photo: Image of Third Fork Creek taken during sampling, showing the creek flowing beneath a bridge and surrounded by dense streamside vegetation.

This publication is part of the RTI Press Research Report series.

RTI International
3040 East Cornwallis Road
Durham, NC
27713-2852

Tel: +1.919.541.6000
E-mail: rtipress@rti.org
Website: www.rti.org

©2026 RTI International. RTI International is a trade name of Research Triangle Institute. RTI, RTI Press, and the RTI logo are U.S. registered trademarks of Research Triangle Institute. Use of RTI Press publications for text and data mining, AI training, and similar technologies is prohibited without RTI's express written permission.



This work is distributed under the terms of a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 license (CC BY-NC-ND), a copy of which is available at <https://creativecommons.org/licenses/by-nc-nd/4.0>

<https://doi.org/10.3768/rtipress.2026.rr.0056.2604>

www.rti.org/rti-press

Contents

About the Authors	iii
Acknowledgments	iv
Abstract	iv
Graphical Abstract	iv
Introduction	1
Materials and Methods	2
Results and Discussion	4
Conclusion	9
Data Availability Statement	10
References	10

About the Authors

Imari Walker-Franklin, PhD, is a natural research scientist in the Analytical Sciences Center at RTI International. <https://orcid.org/0000-0001-9419-320X> (iwalkerfranklin@rti.org)

Julia Apoian, BA, is a chemist in the Analytical Sciences Center at RTI. <https://orcid.org/0009-0000-2020-8245> (japoian@rti.org)

Nateja Hale, MS, is an engineering technician for the City of Winston Salem.

Cana Gerald is a high school student at Cedar Ridge High School.

Porché L. Spence, PhD, is an associate professor of environmental studies at North Carolina Agricultural and Technical State University. <https://orcid.org/0000-0002-3934-0825> (plspence@ncat.edu)

Omar E. Christian, PhD, is a research and lab safety manager at the Office of Environmental Health and Safety at North Carolina State University. <https://orcid.org/0000-0003-4693-6675> (oechrist@ncsu.edu)

Carresse Gerald, PhD, is an assistant professor of environmental, earth, and geospatial sciences at North Carolina Central University. <https://orcid.org/0000-0002-5368-9951> (cgerald6@ncceu.edu)

RTI Press Associate Editor

A. J. Kondash


Acknowledgments

We want to thank the North Carolina Central University–RTI International Center for Applied Research in Environmental Sciences (CARES) program for funding support, Nikki DeLuca for her assistance with the map, and Ashton Grant for her help with consolidation of mass spectral data.

Abstract

Third Fork Creek is an urban tributary in Durham, North Carolina, that drains to Jordan Lake, a regional drinking water supply. Because the last comprehensive chemical survey of this creek was conducted in 2014 and demonstrated poor water quality, we used a combined targeted and non-targeted analysis (NTA) approach to establish an updated baseline of organic contamination and to prioritize analytes for future monitoring. We sampled three sites monthly from July to December 2022. Water samples were filtered, extracted by solid-phase extraction, and analyzed by ultra high-performance liquid chromatography (UHPLC)–Orbitrap high-resolution mass spectrometry (HRMS). In total, 1,346 features were detected (1,043 in positive mode; 303 in negative mode). Spectral library matching returned 43 candidate identifications (29 positive; 14 negative), and mass-list screening provided additional tentative identifications. Principal component analysis showed that temporal (monthly) variation explained more of the compositional differences than spatial location across the three sites. Detected compound classes included pharmaceuticals, per- and polyfluoroalkyl substances (PFAS), plasticizers, biocides, and personal care product residues. Compounds confirmed with analytical standards included atrazine, deisopropyl-atrazine, metolachlor, imidacloprid, sucralose, dibutyl phthalate, caffeine, 6:2 fluorotelomer sulfonate, perfluorooctanesulfonic acid (PFOS), and 4-methylbenzotriazole. Sucralose, a wastewater tracer, ranged from 1.2 to 53.5 nanograms per liter (ng/L) and was highest at the South Alston site in August and October. Suspect screening highlighted several additional priority contaminants for follow-up, including 8-hydroxyquinoline, sildenafil, and oxymetazoline. These results demonstrate that seasonal NTA campaigns can (1) provide a broad, up-to-date contaminant baseline in urban surface waters; (2) reveal temporal pulses and hotspots that routine targeted networks may miss; and (3) generate prioritized target lists to make subsequent routine monitoring and remediation efforts more efficient and cost-effective.

Graphical Abstract



NC = North Carolina; PFAS = per- and polyfluoroalkyl substances; TF = Third Fork.

Key Findings

- A total of 1,346 features were detected in the Third Fork Creek Durham water samples over 6 months.
- Classes of compounds structurally annotated included pharmaceuticals, biocides, polymer additives, and consumer products.
- Presence and intensity of environmental contaminants changed temporally with the highest summed peak areas observed in July, October, and December.
- Seasonal, regional water monitoring using non-targeted analysis can establish a baseline characterization of environmental contamination and guide subsequent prioritized targeted monitoring.

Introduction

Water quality underpins public health, drinking water supplies, fisheries, and biodiversity across North Carolina. The state is home to roughly 10.5 million people, 475 bird species, and 234 freshwater fish species, 57 of which are listed as endangered (North Carolina Wildlife Resources Commission, n.d.). Conventional monitoring programs in the state routinely track physical and biological indicators, such as pH, dissolved oxygen, turbidity, nutrients, bacterial loading, temperature, and salinity, but these parameters do not capture the full range of chemical stressors now present in many watersheds. Rising human activity has introduced diverse pollutants—pesticides, herbicides, heavy metals, per- and polyfluoroalkyl substances (PFAS), industrial chemicals, and polymer additives—that are generally not part of routine monitoring panels (Wang et al., 2024). Targeted chemical campaigns to quantify these contaminants are typically episodic and limited in scope—small, infrequent studies or multiyear surveys—and are resource intensive, often costing hundreds to thousands of dollars per sample, depending on the analyte panel. These constraints limit routine detection of emerging contaminants and increase the likelihood that targeted programs will miss chemicals outside predefined panels as the contamination landscape evolves.

Surface waters in North Carolina, including the Cape Fear River Basin, have long-standing contamination from industrial discharges, wastewater effluent,

agricultural runoff, and urban development; notably, the Cape Fear River has sustained PFAS contamination linked to upstream industrial sources for decades (McCord & Strynar, 2019). These North Carolina surface water systems are also vulnerable to episodic mobilization of pollutants during hurricane season: intense rainfall and flooding increase runoff from roadways and urban areas, flush personal care products and other consumer chemicals into streams, and can release contaminants from compromised wastewater infrastructure and storm-related debris—impacts documented following major storms, such as Hurricane Florence and Hurricane Helene (Aly et al., 2021; Hedgespeth et al., 2021; Walker-Franklin et al., 2025). Third Fork Creek (TFC) is a 16.6-square-mile urban tributary within the Cape Fear River Basin in Durham, North Carolina, that flows into Jordan Lake, a drinking water source and recreational resource. TFC is designated nutrient sensitive and has shown declining indices of water quality—its water quality index dropped from 77 in 2021 to 64 in 2022—driven by elevated bacteria, impaired aquatic life, and nutrient concerns (City of Durham, n.d.; North Carolina Department of Environmental Quality, n.d.). Prior work has likewise identified TFC as impaired (Gerald et al., 2021; Spence, 2015). However, existing monitoring in TFC and similar water systems tends to focus on a limited suite of parameters and may miss anthropogenic organic contaminants that could influence aquatic health and remediation priorities.

Targeted chemical analyses are efficient and sensitive for predefined contaminants but necessarily omit many emerging or unexpected compounds (Pariente et al., 2022). Targeted contaminant surveys (e.g., PFAS or pesticide panels) are generally episodic or short campaigns every few years because of analytical costs. Non-targeted analysis (NTA) using high-resolution mass spectrometry (HRMS) complements targeted methods by screening for hundreds to thousands of known and unknown organic compounds in drinking water, rivers, and streams (Allan et al., 2013; Brack et al., 2019; Ruff et al., 2015; Walker-Franklin et al., 2025). NTA is best viewed as a hypothesis-generating and prioritization tool: it can reveal unmonitored contaminants and potential sources, inform site-specific targeted panels, and help prioritize remediation actions (Kutil et al., 2024). At

the same time, NTA is resource intensive; its greatest value is strategic—that is, it is used to broaden the scope of inquiry where targeted programs indicate impairment or where land use and potential inputs are heterogeneous.

This exploratory study used NTA to characterize spatial and temporal variability in organic contaminant signals in TFC over 6 months. We restricted sampling to July through December 2022 because of resource constraints and a deliberate focus on the wetter summer to fall period during hurricane season when storm-driven runoff and episodic discharges—and thus contaminant mobilization—are most likely. We acknowledge that winter to spring conditions (e.g., lower runoff, different agricultural application schedules, and temperature-dependent chemical behavior) could produce different contaminant profiles and encourage similar sampling in the future. We sampled three sites spanning 5 miles to capture differences in proximity to urban inputs and land use. Our aims were to (1) document site-to-site and seasonal variation in


contaminant composition and abundance and (2) evaluate how NTA results could inform follow-up targeted monitoring and remediation priorities in an already impaired urban creek. We hypothesized that contaminant profiles would vary both spatially and temporally, reflecting localized inputs and episodic events, and that NTA would identify candidate contaminants for prioritized, cost-effective targeted analyses and interventions.

Materials and Methods

Water Sampling

Water samples were collected in three locations along TFC: Site 1 (Park) at Hope Valley Trail (35.938202 N, 78.940282 W), Site 2 (Church) at Elmira Ave./Southside Church of Christ (35.963154 N, -78.901879 W), and Site 3 (S. Alston) at North Carolina Central University (35.970083 N, -78.893596 W), as visualized in the **Figure 1** map. Samples were taken over 12 time points from July 2022 to December 2022 across the three locations. Additional parameters including sample location, date of collection and

Figure 1. Location of sampling sites flowing south (Location 3 to 2 to 1) along the Third Fork Creek in Durham, North Carolina



Note: The three Third Fork Creek sampling locations were Site 1 (Park) at Hope Valley Trail, Site 2 (Church) at Elmira Ave./Southside Church of Christ, and Site 3 (S. Alston) at the North Carolina Central University campus. The chosen locations were accessible sites for sampling and in close proximity to two water quality monitoring stations (Near Public Works Operation Center, 1100 Martin Luther King Jr. Pkwy., Durham, NC 27707) that the City of Durham utilizes.

extraction, water levels, water temperature, pH, conductivity, salinity, and total dissolved solids can be found in the **Supplemental Information (SI) Table S1, SI Figure S1, and SI Figure S2**. Water samples in quantities of 1 liter (L) were gathered from each site in duplicate as grab samples collected in the center of the stream at mid depth using sterilized plastic bottles and were stored on ice after sampling. Samples were transferred to a fridge and stored at 4°C in the dark until preparation for analysis at the same time.

Materials and Reagents


Organic solvents (water, methanol, acetonitrile, & isopropanol) were high-performance (HP) liquid chromatography (LC) grade purity and supplied by Thermo Fisher (Fairlawn, New Jersey). Organic buffers (formic acid and ammonium acetate) were HPLC grade purity and supplied by Sigma Aldrich (St. Louis, Missouri). The 1 surrogate standard, 4 internal standards, and 34 analytical reference standards used had a purity of 94 percent and above (**SI Table S2**). These compounds were sourced from Cambridge Laboratories (Andover, Massachusetts), CDN Laboratories (Langley, British Columbia), TCI

(Portland, Oregon), Thermo Fisher, Sigma Aldrich, Supelco (Bellefonte, Pennsylvania), and Wellington Laboratories (Guelph, Ontario).

Sample Preparation

One liter of each collected water sample, field blank, and laboratory blank was filtered through 2-micrometer pore size Whatman 47-millimeter glass fiber filters, then a surrogate standard, equivalent to 200 nanograms (ng), was added (**Figure 2**). Samples were manually loaded onto 200-milligram Oasis Hydrophilic-Lipophilic Balanced cartridges (Waters Corp, Milford, Mississippi). Extracted samples were eluted using 6 milliliters (mL) of 90:10 methanol:methyl tert-butyl ether. Samples were evaporated to near dryness under nitrogen and reconstituted with 1 mL of 95:5 water:acetonitrile. Quality control pools ($n = 3$) were created by combining aliquots of each sample at all time points. Final samples were spiked with internal standards reaching individual concentrations of 100 ng/mL. After processing, all samples were stored in 2 mL glass vials at -20°C until analysis.

Figure 2. Visualization of the sample preparation, LC-HRMS run and data processing



HLB = Hydrophilic-Lipophilic Balanced; HRMS = high-resolution mass spectrometry; LC = liquid chromatography; MTBE = methyl tert-butyl ether; SPE = solid phase extraction.

LC-HRMS Analysis

Analysis of water samples was completed by ultra high-performance (UHP) LC coupled to HRMS (UHPLC-HRMS) using a Vanquish Flex Liquid Chromatograph and Orbitrap IQX mass spectrometer (Thermo Fisher Scientific, San Jose, California). LC-HRMS data was analyzed using Thermo Scientific Compound Discoverer Version 3.3 to characterize the environmental contaminants prevalent in the water samples. Data were analyzed using an NTA workflow called the “Environmental with Statistics Unknown ID with Online and Local Database Searches,” which was used to detect and identify unknown compounds with differential analysis, comparing groups by location and month sampled. This workflow completed unknown compound detection, retention time alignment, and compound grouping across all samples. Features were retained only if their peak area was at least five times greater than the corresponding signal in the blank; features below this threshold were removed as background. The identification workflow utilized spectral searches against HRMS libraries (including MzCloud, National Institute of Standards and Technology [NIST] tandem mass spectrometry [MS/MS], and RTI International’s in-house library) in silico MS/MS fragmentation (Mass Frontier), compound class assignment (ClassyFire), and exact mass list matches (<5 parts per million [ppm]) to suspect lists (NIST PFAS Mass List, Polymer Additive mass lists, and DSSTox Database; Djoumbou Feunang et al., 2016; Dührkop et al., 2019; Dührkop et al., 2015; Williams et al., 2017). Reference standards were used, where possible, to confirm structural annotations. Confidence levels (1–5) in structural annotation followed the Schymanski workflow (Schymanski et al., 2014). Features were denoted as Level 1 confidence matches by manually matching to a chemical standard’s retention time, parent ion mass accuracy (mass-to-charge ratio [m/z] <5 ppm), and MS/MS fragmentation that was run under the same instrumental conditions. Level 2 confidence was manually annotated to features with parent ion mass accuracy (m/z <5 ppm) and MS/MS fragmentation spectral library matches greater than 70 percent within internal spectral libraries (mzVault) or commercial spectral libraries (mzCloud). Level 3 annotations utilized in silico MS/MS fragmentation

prediction and compound class assignment algorithms to predict chemical class to annotate the chemical. Level 4 annotations were database or mass list matches using the Compound Discoverer’s predicted formula matches or exact mass matches. Additional details on the data processing and the semiquantitation workflow for Level 1 annotations are further detailed in **SI Table S3** and **SI Table S4**.


Statistical Analysis

Volcano plots used differential analysis (t test or analysis of variance) and determined p values (adjusted p values, ratios, fold change, covariance, etc.) to analyze differences between sample groups, including by location and month sampled. Significant features displayed in the volcano plot are plotted by their log-fold change in abundance greater than 2 and $p < 0.05$. Principal component analysis (PCA) was performed between the groups, which identified and grouped samples with similar peaks, assessing the relationship of features between the different sample types. All statistical analysis for quantitation was performed using Prism 10 (GraphPad, San Diego, California). Differences were considered statistically significant at $p < 0.05$. All quantified values are represented as average plus or minus standard deviation ($n = 2$).

Results and Discussion

Characterizing Spatial and Temporal Trends

A PCA in positive mode performed using water samples labeled by month and location visually displayed similarities and variances between sample types (**Figure 3**). The PCA plot illustrated that water samples had very little difference based on location in positive mode; however, the Park samples clustered more closely in negative mode PCA plots (**SI Figure S3**). Loading plots from the PCA and differential analysis plots demonstrated that there were clusters of features likely driving differences in the samples. Regarding differences by month sampled, there were significant isolated clusters observed in July, October, and December 2022 within both positive and negative mode plots. The months of August, September, and November primarily clustered together. This difference was further confirmed

Figure 3. Principal component analysis plot colored by location (left) and month (right) sampled

PC = principal component.

Note: Data were from positive mode and demonstrated that the chemical features cluster more by month sampled, less by location.


by comparing the positive ion max summed peak area abundance by month, where October (1.22E9), July (1.11E9), and December (9.25E8) had the highest values out of all months (SI Excel File S6). The differences in feature abundances and type by month sampled may be accounted for by weather pattern changes and anthropogenic contaminant use patterns. Observations of stream water quantity recorded by the US Geological Survey (USGS) TFC water monitoring station demonstrate clear spikes in gauge height for TFC in the months of July, October, and December, which indicate increased inputs of water into the system and potential mobilization of contaminants. July had the highest average rainfall (7.69 inches) and warmest average water temperatures (25°C; National Centers for Environmental Information, n.d.). The combination of warm temperatures, rainfall, and commonly increased human activity was very likely to have released a variety of chemical micropollutants. Water quality parameters tested during sampling in July had, on average, the highest salinity and total dissolved solids, indicating the potential for contaminants. October was the driest month of the time points sampled (1.14 inches of precipitation) but the highest month for water levels in the creek, indicating other upstream influences on water levels and contaminant mobilization. Previous studies looking at temporal and spatial differences in water contamination showed the dry season had the highest abundance of contamination in Grand Canal, China (Xiaolong et al., 2010).

NTA detected 1,043 features in positive mode and 303 in negative mode (SI Table S5). Pairwise differential analyses (volcano plots; $p < 0.05$ and $|\log_2 \text{fold change}| > 1$) identified features that differed significantly both among months and between sampling locations (SI Figure S4). In site-to-site comparisons, Park samples exhibited the largest number of features whose abundances differed significantly from those in the South Alston and Church samples. This pattern is consistent with the land use context shown in Figure 4: the Park site is dominated by open parkland and vacant lots adjacent to residential areas, whereas the Church site is surrounded by commercial and residential development and South Alston is a more heavily urbanized area adjacent to North Carolina Central University. Together, these results indicate that, though temporal variation was a major driver of compositional change, spatial differences linked to local land use also produce distinct contaminant signatures.

Annotation of Emerging Contaminants

High-resolution MS/MS spectra from the samples were matched against curated tandem mass spectral libraries (MzCloud, NIST, and RTI in-house libraries) to structurally annotate 29 positive-mode and 14 negative-mode features. Analytical standards were used to confirm several compound identities. After collapsing duplicate features (retaining the feature with the highest maximum peak area), 31 unique compounds are summarized in Figure 5. These putative and confirmed contaminants span pharmaceuticals, biocides, plastic additives, and

Figure 4. Land use maps of the North Carolina Cape Fear River Basin, including Third Fork Creek and the surrounding areas near the three sample locations (Park, Church, and S. Alston)



GIS = geographic information system; NC = North Carolina.

personal care product residues; several—atrazine, deisopropyl-atrazine, metolachlor, imidacloprid, sucralose, and 4-methylbenzotriazole—have previously been detected in nearby groundwater (Apex, North Carolina), illustrating the regional ubiquity of these contaminants (Hunter et al., 2021). Using PubChem hazard annotations, 21 of the 31 compounds were flagged as potentially harmful to aquatic organisms or human health. This finding is consistent with prior NTA surveys of US streams that linked numerous detected features to bioactive effects in vitro (Blackwell et al., 2018), underscoring the utility of NTA for prioritizing compounds for follow-up confirmation and risk assessment.

In **Figure 5**, maximum peak area patterns by location and month showed that the pharmaceuticals did not peak simultaneously in a single month; however,

four of six pharmaceuticals had their highest peak areas in Park samples. Although the Park site is not adjacent to treatment plants or landfills (**SI Table S6**), these detections are consistent with some degree of wastewater influence (e.g., upstream inputs, septic leakage, illicit human discharges, or stormwater conveyance) in that reach of TFC. More than half (14 of 22) of the consumer product and plastic additive compounds were most abundant at the South Alston site in July 2022. South Alston is the most urbanized sampling location—adjacent to the university, the Durham County Construction & Demolition Landfill, and the North Durham Water Reclamation Facility (**SI Table S6**)—and July was the warmest and wettest month sampled, coinciding with peak local construction activity (Belayutham et al., 2016). Increased human activity, higher temperatures, and

Figure 5. Level 1 and Level 2 annotated confidence level environmental contaminants detected within the water samples

Name	Conf. Level	Formula	CAS	Spectral Library Score	Function/Use	Aquatic Toxin	Acute Toxin	Area (Max)	July	Aug.	Sept.	Oct.	Nov.	Dec.	Location (Max Area)	Log Kow (+/-)
Pharmaceutical																
17 α -Methyl-androstan-3-hydroxyimino-17 β -ol	2	C ₂₀ H ₃₃ NO ₂	2722-75-0	84	Steroid, Drug			2.29E+07							Park	+ 4.2
Oxymetazoline	2	C ₁₆ H ₂₃ N ₂ O	1491-59-4	70	Nasal Decongestant	x	x	1.15E+07							Park	+ 4.9
Adenosine	2	C ₁₀ H ₁₃ N ₅ O ₄	364-62-5	86	Anti-arrhythmia drug, Vasodilator agent, Analgesic			1.24E+06							Church	+ 2.6
Scoparone	2	C ₁₁ H ₁₀ O ₄	120-08-1	76	Antioxidant, Vasodilator, Anti-Arhythmia		x	9.54E+05							Church	+ 1.3
Sildenafil	2	C ₂₂ H ₃₀ N ₆ O ₄ S	139755-83-2	80	Erectile Dysfunction Treatment	x	x	5.84E+05							Park	+ 2.8
Metoclopramide	2	C ₁₄ H ₂₂ ClN ₂ O ₂	364-62-5	77	Gastrointestinal Drug		x	5.82E+05							Park	+ 2.6
Biocides																
Desisopropylatrazine	1	C ₉ H ₈ ClN ₃	1007-28-9	77	Pesticide, Transformation Products	x	x	2.08E+07							Park	+ 1.1
Metolachlor	1	C ₁₁ H ₂₂ ClNO ₂	51218-45-2	80	Herbicide	x	x	4.06E+05							Church	+ 3.1
Imidacloprid	1	C ₉ H ₁₀ ClN ₂ O ₂	138261-41-3	N/F	Insecticide	x		2.36E+05							S. Alston	- 0.57
Plastic Additives																
Dibutyl phthalate	1	C ₁₆ H ₂₂ O ₄	84-74-2	56	Plasticizer	x		3.72E+06							S. Alston	- 4.5
6:2 Fluorinated telomer sulfonate	1	C ₈ H ₄ F ₁₃ O ₃ S	27619-97-2	78	PFAS, Plastics, Consumer Products		x	9.34E+06							Church	- 3.9
Perfluorooctanesulfonic acid	1	C ₈ HF ₁₇ O ₃ S	1763-23-1	85	PFAS, Plastics, Consumer Products	x	x	9.22E+04							Park	- 4.5
N,N-Dimethylacetamide	2	C ₄ H ₉ NO	127-19-5	73	Paint and Polymer Additive, Solvent		x	1.38E+08							S. Alston	+ -0.7
N,N'-Diphenylguanidine	2	C ₁₃ H ₁₃ N ₃	20277-92-3	90	Tire additive			8.74E+06							S. Alston	+ 1.6
Tris(2-butoxyethyl) Phosphate	2	C ₁₈ H ₃₉ O ₃ P	78-51-3	80	Plasticizer, Flame Retardant		x	9.05E+07							S. Alston	+ 3.8
Tris(3-Chloropropyl) Phosphate	2	C ₉ H ₁₈ Cl ₃ O ₃ P	1067-98-7	71	Flame retardant			5.14E+07							S. Alston	+ 2.0
Consumer Products																
Sucralose	1	C ₁₈ H ₁₉ Cl ₃ O ₈	56038-13-2	N/F	Sweetener	x	x	8.79E+04							S. Alston	- -1.0
4-Methylbenzotriazole	1	C ₇ H ₇ N ₃	29878-31-7	93	Corrosion Inhibitor, Transformation Product	x	x	1.36E+07							Church	(+/-) 1.4
Galaxolidone	2	C ₁₈ H ₂₄ O ₂	507442-49-1	84	Fragrance Metabolites			4.56E+06							Park	+ 5.0
8-Hydroxyquinoline	2	C ₉ H ₇ NO	148-24-3	82	Antiseptic, Corrosion Inhibitor, Fungicide, Dyes	x	x	1.55E+06							Park	+ 2.0
10-(4-Sulfophenyl) decanoic acid	2	C ₁₆ H ₂₄ O ₃ S	N/F	87	Surfactant			5.57E+05							S. Alston	- 3.9
cis-7-Hexadecenoic acid	2	C ₁₆ H ₃₀ O ₂	2416-19-5	93	Surfactant			2.70E+07							S. Alston	- 6.6
Dodecamethylcyclohexasiloxane	2	C ₁₂ H ₃₆ O ₆ Si ₆	540-97-6	83	Cosmetics, Industrial Product Use	x		1.15E+07							Church	+ 8.8
Dodecyl sulfate	2	C ₁₂ H ₂₆ O ₄ S	151-41-7	91	Cosmetics, Wastewater Treatment			6.17E+06							S. Alston	- 4.7
Cetrimonium	2	C ₁₉ H ₄₁ N	6899-10-1	97	Personal Care Product, Antiseptic			3.24E+07							S. Alston	+ 8.0
Hexadecanamide	2	C ₁₆ H ₃₃ NO	629-54-9	95	Fatty Acid, Cleaning product metabolite	x		4.35E+07							Park	+ 6.2
Oleamide	2	C ₁₈ H ₃₅ NO	301-02-0	94	Slip and Anti-block Agent for Plastics, Cosmetics	x		1.73E+08							Church	+ 6.6
Myristyl sulfate	2	C ₁₄ H ₃₀ O ₄ S	4754-44-3	77	Wetting Agent, Sclerosing Agent, Treats Varicose Vein		x	1.09E+06							S. Alston	- 5.8
Xylenesulfonate	2	C ₈ H ₁₀ O ₃ S	1300-72-7	88	Multiple Uses, Consumer Products, Auto Products			3.27E+06							S. Alston	- 1.9
PEG n13	2	C ₂₆ H ₅₄ O ₁₄	9005-00-9	75	Multiple Uses, Medicine, Consumer Products			3.19E+06							S. Alston	+ 8.4
PPG n10	2	C ₃₀ H ₆₂ O ₁₁	148-24-3	79	Consumer and Industrial Product			1.89E+06							S. Alston	+ NA

CAS = chemical abstracts services registry number; N/F = not found; PEG = polyethylene glycol; PFAS = per- and polyfluoroalkyl substances; PPG = polypropylene glycol.

Note: PubChem was used to determine chemical use, Log Kow, and toxicity. Polarity was defined in the column (+/-). The accompanying heatmap displays relative peak area abundance across the months sampled, with red indicating the highest, white the median, and blue the lowest peak area levels per compound. Pharmaceuticals vary by time and are most abundant in the Park samples. Biocides vary by location and time, perhaps due to application at different locations and times. Plastic additives and consumer products are most present in July and South Alston. Construction was occurring near South Alston during the time of collection.

stormwater runoff likely contributed to the elevated July signals for urban-associated chemicals, such as the tire additive diphenyl guanidine (Obanya et al., 2024). For features without confident spectral matches, we selected the top 322 nonduplicate positive-mode peaks with available tandem mass spectra and classified them using ClassyFire. Most of these unannotated features were assigned to classes typical of natural organic matter (organic acids, heterocyclic compounds, lipids, and benzenoids; SI

Figure S5; SI Table S7), suggesting a mix of biogenic and anthropogenic inputs in the creek's chemical signature.

Trends of Emerging Contaminants

Surface waters are commonly subjected to increasing stress as related to anthropogenic activities. Within the water samples analyzed, 9 of the 23 targeted chemical pollutants were detected and semiquantified from exact parent mass within each time point


and location using chemical reference standards, retention time, and parent mass (**Figure 6** and **SI Excel File S3**). Chemical classes of those quantitated over time included herbicides, pesticides, polymer additives, PFAS, and personal care compounds. Concentrations for these analytes had varied by time and location: atrazine (1.0–3.1 ng/L), 4,8-dioxa-3H-perfluorononanoic acid (ADONA; 1.4–3.9 ng/L), dibutyl phthalate (0.7– 8.9 ng/L), caffeine (1.0–6.78 ng/L), imidacloprid (1.0–27.3 ng/L), atrazine desisopropyl (1.1–47.8 ng/L), sucralose (1.2–53.5 ng/L), 6:2 fluorotelomer sulfonate (FTS; 1.6–83.6 ng/L), and methyl benzotriazole (1.1–375.6 ng/L). Spearman correlation analysis (**SI Figure S6**) showed that water temperature was negatively associated with pH, as well as concentrations of ADONA, 6:2 FTS, and methylbenzotriazole. In contrast, temperature and rainfall were positively associated with dibutyl phthalate, caffeine, and imidacloprid. These patterns indicate that routine physicochemical parameters alone do not reliably predict the occurrence or abundance of specific organic contaminants, underscoring the value of complementary chemical screening to capture pollutant dynamics.

Sucralose did not show strong Spearman correlations with routine water quality parameters, but it covaried with other indicators of wastewater influence like caffeine, a contaminant commonly studied in TFC (Spence, 2015). Sucralose reached a maximum of 53.5 ng/L at the South Alston site in October. Reported concentrations in the literature vary by setting: treated wastewater effluent is typically in the low microgram (μg)/L range (roughly hundreds to a

few thousand ng/L; Subedi & Kannan, 2014), source waters for drinking water treatment plants have been reported from tens to several thousand ng/L (Mawhinney et al., 2011), and surface water levels range from single digit ng/L in minimally impacted areas to $\mu\text{g}/\text{L}$ levels in effluent-dominated reaches (Heider et al., 2018). Thus, the 53.5 ng/L measured here is consistent with a detectable wastewater signal but is lower than typical effluent concentrations. Four pharmaceuticals were tentatively identified, with their largest peak areas also observed at South Alston, suggesting this site experienced the greatest influence from wastewater-derived inputs (Buerge et al., 2009). Temporal patterns, however, were not consistent across tracers: peak areas and concentrations of sucralose, caffeine, and the detected pharmaceuticals did not align across all sampling dates (Whitall et al., 2021). Differences in human metabolism and environmental persistence likely account for these discrepancies—sucralose is comparatively recalcitrant and persists longer in the environment than caffeine and many pharmaceuticals, which are more rapidly metabolized and degraded (Grice & Goldsmith, 2000; Roberts et al., 2000; Tollefsen et al., 2012). Consequently, cooccurrence of multiple tracers supports a wastewater signal at South Alston, but asynchronous temporal trends highlight the value of using several complementary indicators and repeated sampling to characterize inputs.

In addition to wastewater tracers, we quantified other contaminant classes over time—notably, the herbicide atrazine and its metabolite, deisopropyl-atrazine. Atrazine was measured at low but variable levels

Figure 6. Concentration of analytes semiquantified over time: (A) atrazine, (B) caffeine, and (C) sucralose



Note: Concentrations of compounds below the limit of detection are depicted at concentrations of the limit of detection divided by the square root of 2.

and peaked in late October; deisopropyl-atrazine, which forms primarily by microbial N-dealkylation of atrazine, reached higher concentrations with peaks in November to December. This lag between parent and metabolite is consistent with biotransformation timescales that can range from days to months, depending on temperature, microbial adaptation, and hydrologic conditions. Although observed atrazine concentrations were well below the US Environmental Protection Agency's drinking water maximum contaminant level of 3,000 ng/L, atrazine's mobility, persistence, endocrine-related effects, and aquatic toxicity support continued monitoring of both the parent compound and its metabolites.

PFAS—a broad class of more than 16,000 fluorinated compounds used in firefighting foams, grease- and stain-resistant products, and many industrial applications—were also detected (Habib et al., 2024). Perfluorooctanesulfonic acid (PFOS) was observed by HRMS with the largest peak area signal in the Park samples from September, but it did not exceed our limit of quantitation (1 ng/mL). Two other PFAS, ADONA and 6:2 FTS, were quantified and reached maximum concentrations in December at the Church site (ADONA: 3.9 ng/L; 6:2 FTS: 83.6 ng/L). Although these values do not exceed common regulatory thresholds, their persistence and potential for effects on ecology and human health (including immune, reproductive, and endocrine impacts and associations with certain cancers for some PFAS) justify continued surveillance and, where appropriate, follow-up targeted analyses. The differing peak times among PFAS also suggest multiple sources or input pathways. Water basin scale analysis from 2018 to 2020 found PFOS among the more frequently quantified analytes and detected 6:2 FTS above the limit of detection in a majority of samples—though sites near Jordan Lake showed lower average concentrations than other locations—underscoring the value of site-specific monitoring to identify local hotspots and prioritize management (Pétre et al., 2022).

TFC Chemical Contaminant Comparison to 2014 USGS Study

The USGS previously conducted a targeted screening of TFC (April–June 2014; 10 sampling events; **SI Excel File S7**), analyzing 107 pharmaceuticals and

230 pesticides but quantifying only 9 pharmaceuticals and 49 pesticides. This outcome illustrates a practical limitation of broad targeted panels: they can be costly in materials and labor while yielding low detection rates when many analytes are absent or below quantitation limits. For compounds common to both studies, concentrations in our samples—caffeine (30–332 ng/L), atrazine (2.8–86.1 ng/L), and methyl-1H-benzotriazole (205–887 ng/L)—were similar to or lower than the USGS values. Such differences likely reflect methodological factors (our extraction protocol prioritized recovery across multiple chemical classes, and our results are semiquantitative), seasonal and hydrologic variation between sampling campaigns, and differences in analytical sensitivity. A key contribution of our work is that the HRMS non-targeted workflow detected 34 compounds at confidence Level 1 or Level 2, of which 30 were not reported in the 2014 USGS survey (USGS, 2014). More than a decade has passed since the USGS organic chemical screening of TFC, so renewed monitoring is warranted. Several compounds newly detected in our study—8hydroxyquinoline, sucralose, PFOS, metolachlor, sildenafil, and oxymetazoline—should be prioritized for followup targeted analyses and incorporated into future USGS and state monitoring programs to confirm concentrations and assess potential human health and ecological risks.

Conclusion

This exploratory study found that TFC exhibited pronounced monthly variability but only modest differences across the three sampling sites. Over the 6-month campaign, we detected roughly 1,300 distinct features, and structural annotation indicated diverse classes, including pharmaceuticals, biocides, polymer additives, and consumer product residues. Chemical signals associated with wastewater, agricultural management, and construction were most pronounced at the South Alston site, which showed the highest overall chemical burden in October—likely reflecting elevated creek levels and storm-driven runoff at that time. Because more than a decade has passed since the last USGS chemical screen, our NTA campaign establishes an updated, broad baseline for TFC contamination and identifies candidate compounds for follow-up.

We acknowledge that once priority analytes are identified, routine targeted analyses are generally more cost-effective for ongoing surveillance. However, NTA has distinct and lasting value: it enables discovery of unexpected or emerging contaminants and transformation products that targeted panels miss, it captures complex mixtures useful for source apportionment and risk screening, and it provides the evidence base needed to design efficient targeted monitoring programs and remediation priorities. For practical monitoring, we

therefore recommend a hybrid approach: periodic NTA campaigns (e.g., after major land use changes, storms, or multiyear intervals) to update the target list, combined with more frequent, lower-cost targeted sampling for the prioritized contaminants.

Data Availability Statement

The data supporting the current study are available on Zenodo at <https://zenodo.org/records/18663398>.

References

- Allan, I. J., Harman, C., Ranneklev, S. B., Thomas, K. V., & Grung, M. (2013). Passive sampling for target and nontarget analyses of moderately polar and nonpolar substances in water. *Environmental Toxicology and Chemistry*, 32(8), 1718–1726. <https://doi.org/10.1002/etc.2260>
- Aly, N. A., Casillas, G., Luo, Y.-S., McDonald, T. J., Wade, T. L., Zhu, R., Newman, G., Lloyd, D., Wright, F. A., Chiu, W. A., & Rusyn, I. (2021). Environmental impacts of Hurricane Florence flooding in eastern North Carolina: Temporal analysis of contaminant distribution and potential human health risks. *Journal of Exposure Science & Environmental Epidemiology*, 31(5), 810–822. <https://doi.org/10.1038/s41370-021-00325-5>
- Belayutham, S., González, V. A., & Yiu, T. W. (2016). The dynamics of proximal and distal factors in construction site water pollution. *Journal of Cleaner Production*, 113, 54–65. <https://doi.org/10.1016/j.jclepro.2015.11.075>
- Blackwell, B. R., Ankley, G. T., Bradley, P. M., Houck, K. A., Makarov, S. S., Medvedev, A. V., Swintek, J., & Villeneuve, D. L. (2018). Potential toxicity of complex mixtures in surface waters from a nationwide survey of United States streams: Identifying in vitro bioactivities and causative chemicals. *Environmental Science & Technology*, 53(2), 973–983. <https://doi.org/10.1021/acs.est.8b05304>
- Brack, W., Hollender, J., de Alda, M. L., Müller, C., Schulze, T., Schymanski, E., Slobodnik, J., & Krauss, M. (2019). High-resolution mass spectrometry to complement monitoring and track emerging chemicals and pollution trends in European water resources. *Environmental Sciences Europe*, 31, Article 62. <https://doi.org/10.1186/s12302-019-0230-0>
- Buerge, I. J., Buser, H. R., Kahle, M., Müller, M. D., & Poiger, T. (2009). Ubiquitous occurrence of the artificial sweetener acesulfame in the aquatic environment: An ideal chemical marker of domestic wastewater in groundwater. *Environmental Science & Technology*, 43(12), 4381–4385. <https://doi.org/10.1021/es900126x>
- City of Durham. (n.d.). *Third Fork Creek*. <https://www.durhamnc.gov/774/Third-Fork-Creek>
- Djombou Feunang, Y., Eisner, R., Knox, C., Chepelev, L., Hastings, J., Owen, G., Fahy, E., Steinbeck, C., Subramanian, S., Bolton, E., Greiner, R., & Wishart, D. S. (2016). ClassyFire: Automated chemical classification with a comprehensive, computable taxonomy. *Journal of Cheminformatics*, 8, Article 61. <https://doi.org/10.1186/s13321-016-0174-y>
- Dührkop, K., Fleischauer, M., Ludwig, M., Aksenov, A. A., Melnik, A. V., Meusel, M., Dorrestein, P. C., Rousu, J., & Böcker, S. (2019). SIRIUS 4: A rapid tool for turning tandem mass spectra into metabolite structure information. *Nature Methods*, 16(4), 299–302. <https://doi.org/10.1038/s41592-019-0344-8>

- Dührkop, K., Shen, H., Meusel, M., Rousu, J., & Böcker, S. (2015). Searching molecular structure databases with tandem mass spectra using CSI:FingerID. *Proceedings of the National Academy of Sciences of the United States of America*, 112(41), 12580–12585. <https://doi.org/10.1073/pnas.1509788112>
- Gerald, C., Deshazo, B., Patterson, H., & Spence, P. (2021). *Using Caenorhabditis elegans as an environmental indicator for impaired urbanized watersheds* [Manuscript submitted for publication]. Research Square. <https://doi.org/10.21203/rs.3.rs-885715/v1>
- Grice, H. C., & Goldsmith, L. A. (2000). Sucralose—An overview of the toxicity data. *Food and Chemical Toxicology*, 38(Suppl. 2), 1–6. [https://doi.org/10.1016/S0278-6915\(00\)00023-5](https://doi.org/10.1016/S0278-6915(00)00023-5)
- Habib, Z., Song, M., Ikram, S., & Zahra, Z. (2024). Overview of per- and polyfluoroalkyl substances (PFAS), their applications, sources, and potential impacts on human health. *Pollutants*, 4(1), 136–152. <https://doi.org/10.3390/pollutants4010009>
- Hedgspeth, M. L., McCord, J. P., Phillips, K. A., Strynar, M. J., Shea, D., & Nichols, E. G. (2021). Suspect-screening analysis of a coastal watershed before and after Hurricane Florence using high-resolution mass spectrometry. *Science of the Total Environment*, 782, Article 146862. <https://doi.org/10.1016/j.scitotenv.2021.146862>
- Heider, E. C., Valenti, D., Long, R. L., Garbou, A., Rex, M., & Harper, J. K. (2018). Quantifying sucralose in a water-treatment wetlands: Service-learning in the analytical chemistry laboratory. *Journal of Chemical Education*, 95(4), 535–542. <https://doi.org/10.1021/acs.jchemed.7b00490>
- Hunter, B., Walker, I., Lassiter, R., Lassiter, V., Gibson, J. M., Ferguson, P. L., & Deshusses, M. A. (2021). Evaluation of private well contaminants in an underserved North Carolina community. *Science of the Total Environment*, 789, Article 147823. <https://doi.org/10.1016/j.scitotenv.2021.147823>
- Kutil, Z., Novotna, K., Cermakova, L., & Pivokonsky, M. (2024). Tunnel vision in the drinking water research field—Time for non-targeted analysis implementation? *Science of the Total Environment*, 908, Article 168367. <https://doi.org/10.1016/j.scitotenv.2023.168367>
- Mawhinney, D. B., Young, R. B., Vanderford, B. J., Borch, T., & Snyder, S. A. (2011). Artificial sweetener sucralose in U.S. drinking water systems. *Environmental Science & Technology*, 45(20), 8716–8722. <https://doi.org/10.1021/es202404c>
- McCord, J., & Strynar, M. (2019). Identification of per- and polyfluoroalkyl substances in the Cape Fear River by high resolution mass spectrometry and nontargeted screening. *Environmental Science & Technology*, 53(9), 4717–4727. <https://doi.org/10.1021/acs.est.8b06017>
- National Centers for Environmental Information. (n.d.). *Local Climatological Data (LCD)*. U.S. Department of Commerce, National Oceanic and Atmospheric Administration. <https://www.ncei.noaa.gov/products/land-based-station/local-climatological-data>
- North Carolina Department of Environmental Quality. (n.d.). *Classifications*. <https://www.deq.nc.gov/about/divisions/water-resources/water-planning/classification-standards/classifications>
- North Carolina Wildlife Resources Commission. (n.d.). *Species*. Retrieved October 16, 2025, from <https://www.ncwildlife.gov/wildlife-habitat/species>
- Obanya, H. E., Khan, F. R., Carrasco-Navarro, V., Rødland, E. S., Walker-Franklin, I., Thomas, J., Cooper, A., Molden, N., Amaeze, N. H., Patil, R. S., Kukkola, A., Michie, L., Green-Ojo, B., Rauert, C., Couceiro, F., Hutchison, G. R., Tang, J., Ugor, J., Lee, S.,...Ford, A. T. (2024). Priorities to inform research on tire particles and their chemical leachates: A collective perspective. *Environmental Research*, 263(Part 3), Article 120222. <https://doi.org/10.1016/j.envres.2024.120222>
- Pariente, M. I., Segura, Y., Álvarez-Torrellas, S., Casas, J. A., de Pedro, Z. M., Diaz, E., García, J., López-Muñoz, M. J., Marugán, J., Mohedano, A. F., Molina, R., Munoz, M., Pablos, C., Perdígón-Melón, J. A., Petre, A. L., Rodríguez, J. J., Tobajas, M., & Martínez, F. (2022). Critical review of technologies for the on-site treatment of hospital wastewater: From conventional to combined advanced processes. *Journal of Environmental Management*, 320, Article 115769. <https://doi.org/10.1016/j.jenvman.2022.115769>

- Pétre, M.-A., Salk, K. R., Stapleton, H. M., Ferguson, P. L., Tait, G., Obenour, D. R., Knappe, D. R. U., & Genereux, D. P. (2022). Per- and polyfluoroalkyl substances (PFAS) in river discharge: Modeling loads upstream and downstream of a PFAS manufacturing plant in the Cape Fear watershed, North Carolina. *Science of the Total Environment*, 831, Article 154763. <https://doi.org/10.1016/j.scitotenv.2022.154763>
- Roberts, A., Renwick, A. G., Sims, J., & Snodin, D. J. (2000). Sucralose metabolism and pharmacokinetics in man. *Food and Chemical Toxicology*, 38(Suppl. 2), 31–41. [https://doi.org/10.1016/S0278-6915\(00\)00026-0](https://doi.org/10.1016/S0278-6915(00)00026-0)
- Ruff, M., Mueller, M. S., Loos, M., & Singer, H. P. (2015). Quantitative target and systematic non-target analysis of polar organic micro-pollutants along the river Rhine using high-resolution mass-spectrometry—Identification of unknown sources and compounds. *Water Research*, 87, 145–154. <https://doi.org/10.1016/j.watres.2015.09.017>
- Schymanski, E. L., Jeon, J., Gulde, R., Fenner, K., Ruff, M., Singer, H. P., & Hollender, J. (2014). Identifying small molecules via high resolution mass spectrometry: Communicating confidence. *Environmental Science & Technology*, 48(4), 2097–2098. <https://doi.org/10.1021/es5002105>
- Spence, P. L. (2015). Using caffeine as a water quality indicator in the ambient monitoring program for Third Fork Creek Watershed, Durham, North Carolina. *Environmental Health Insights*, 9(Suppl. 2), 29–34. <https://doi.org/10.4137/EHI.S19588>
- Subedi, B., & Kannan, K. (2014). Fate of artificial sweeteners in wastewater treatment plants in New York State, U.S.A. *Environmental Science & Technology*, 48(23), 13668–13674. <https://doi.org/10.1021/es504769c>
- Tollefsen, K. E., Nizzetto, L., & Huggett, D. B. (2012). Presence, fate and effects of the intense sweetener sucralose in the aquatic environment. *Science of the Total Environment*, 438, 510–516. <https://doi.org/10.1016/j.scitotenv.2012.08.060>
- U.S. Geological Survey. (2014). *Water quality and quantity data for monitoring location Third Fork CR at Woodcroft Parkway NR Blands, NC (USGS-02097280), April to June 2014*. <https://waterdata.usgs.gov/download-samples/#monitoringLocationIdentifier=USGS-02097280&dataProfile=fullphyschem>
- Walker-Franklin, I., Blake, S., Thorp, E., & Tuberty, S. (2025). Preliminary identification of PFAS and other emerging contaminants in the French Broad River, NC post-Hurricane Helene. *Toxics*, 13(11), 905. <https://doi.org/10.3390/toxics13110905>
- Wang, R., Tang, H., Yang, R., & Zhang, J. (2024). Emerging contaminants in water environments: Progress, evolution, and prospects. *Water Science & Technology*, 89(10), 2763–2782. <https://doi.org/10.2166/wst.2024.151>
- Whitall, D., Curtis, M., & Mason, A. (2021). Use of sucralose and caffeine as tracers of human waste in a coral reef ecosystem. *Regional Studies in Marine Science*, 44, Article 101740. <https://doi.org/10.1016/j.rsma.2021.101740>
- Williams, A. J., Grulke, C. M., Edwards, J., McEachran, A. D., Mansouri, K., Baker, N. C., Patlewicz, G., Shah, I., Wambaugh, J. F., Judson, R. S., & Richard, A. M. (2017). The CompTox Chemistry Dashboard: A community data resource for environmental chemistry. *Journal of Cheminformatics*, 9, Article 61. <https://doi.org/10.1186/s13321-017-0247-6>
- Xiaolong, W., Jingyi, H., Ligang, X., & Qi, Z. (2010). Spatial and seasonal variations of the contamination within water body of the Grand Canal, China. *Environmental Pollution*, 158(5), 1513–1520. <https://doi.org/10.1016/j.envpol.2009.12.018>

RTI International is an independent scientific research institute dedicated to improving the human condition. We combine scientific rigor and technical expertise in social and laboratory sciences, engineering, and international development to deliver solutions to the critical needs of clients worldwide.

www.rti.org/rtipress

RTI Press publication RR-0056-2604