INFRASTRUCTURE FOR BIODIVERSITY CONSERVATION IN KIDEPO VALLEY NATIONAL PARK

VOLUME OF DRAWINGS

Construction of Low Water Stream Crossings Structures at "Kalabe, Kurao, Lopiripir, and Tongbore"

Prepared by: USAID / Uganda Architect & Engineering Design and Construction Management Services Implemented by: MBW Consulting Ltd. and Cardno I.D. USA

LIST OF DRAWINGS AND GENERAL NOTES

INFRASTRUCTURE FOR BIODIVERSITY CONSERVATION IN KIDEPO VALLEY NP - LOW WATER STREAM CROSSINGS (LWSC) LIST OF DRAWINGS

Drawing Description	Drawing No.	Revision
LIST OF DRAWINGS AND GENERAL NOTES		
List of General Notes_ General Notes	906-01-DWG-GN-001	
List of General Notes_ General Notes 2	906-01-DWG-GN-002	
List of General Notes_ General Notes 2	906-01-DWG-GN-003	
LOW WATER STREAM CROSSINGS (LWSC)		
LOCATION MAP		
Location Map _ LWSC	906-01-DWG-C-GD-002	
TYPICAL DRAWINGS OF LWSC AND APPROACH ROADS		
LWSC & Approach Roads : Typical Approach Road Sections_01	906-01-DWG-C-T5-001	
LWSC \$ Approach Roads : Typical Approach Road Sections_02	906-01-DWG-C-T5-002	
KALABE LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
Plan \$ Longitudinal Profile : Kalabe LWSC \$ Approach Roads	906-01-DWG-C-PP-001	
Plan & Longitudinal Profile : Kalabe LWSC River Profile	906-01-DWG-C-PP-001.2	
Plan & Longitudinal Profile : Kalabe LWSC River Protection	906-01-DWG-C-PP-001.3	
Details LWSC & Approach Roads Detail O I : Typical River Scour	906-01-DWG-C-T5-001.4	
Protection for Kalabe LWSC & Approach Roads : Structural Plan & Longitudinal Details	906-01-DWG-C-T5-001.5	
or Kalabe LWSC & Approach Roads : Structural Sectional Details for	906-01-DWG-C-TS-001.6	=
Salabe LWSC \$ Approach Roads : 2 Cell Box Culvert details for Kalabe	906-01-DWG-C-TS-001.7	
KURAO LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
Plan \$ Longitudinal Profile : Kurao LWSC \$ Approach Roads	906-01-DWG-C-PP-002	NOTES 4
LWSC \$ Approach Roads Detail 02: Typical River Scour	906-01-DWG-C-T5-002.2	
Protection for Kurao LWSC & Approach Roads : Structural Plan & Longitudinal Details	906-01-DWG-C-T5-002.3	A compa
or Kurao LWSC \$ Approach Roads : Structural Sectional Details for Kuraa	906-01-DWG-C-TS-002.4	
LOPIRIPIR LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
Plan \$ Longitudinal Profile : Lopiripir LWSC \$ Approach Roads	906-01-DWG-C-PP-003	~
LWSC \$ Approach Roads : Detail 03 for Lopiripir	906-01-DWG-C-T5-003.2	
LWSC & Approach Roads : Structural Plan & Longitudinal Details	906-01-DWG-C-T5-003.3	
or Lopinipir LWSC	906-01-DWG-C-TS-003.4	
opiripir		

Drawing Description	Drawing No.	Revision
NAKAO LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
	000 01 0110 0 00 001	
Plan \$ Longitudinal Profile : Nakao LWSC \$ Approach Roads	906-01-DWG-C-PP-004	
LWSC \$ Approach Roads : Detail O4 for Nakao LWSC	906-01-DWG-C-T5-004.2	
LWSC \$ Approach Roads : Structural Plan \$ Longitudinal Details or Nakao	906-01-DWG-C-TS-004.3	
LWSC	906-01-DWG-C-T5-004.4	
TONGBORE LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
Plan & Longitudinal Profile : Tongbore LWSC & Approach Roads	906-01-DWG-C-PP-005	
LWSC # Approach Roads : Detail O5 for Tongbore LWSC	906-01-DWG-C-T5-005.2	
LWSC	906-01-DWG-C-T5-005.3	
LWSČ & Approach Roads : Structural Sectional Details for	906-01-DWG-C-TS-005.4	
「ongbore LWSC	906-01-DWG-C-T5-005.5	
KIDEPO LWSC		
PLAN AND PROFILE OF LWSC AND APPROACH ROADS		
Plan \$ Longitudinal Profile : Kidepo LWSC \$ Approach Roads _	906-01-DWG-C-PP-006A	
Option Plan \$ Longitudinal Profile : Kidepo LWSC \$ Approach Roads		
Option Plan \$ Longitudinal Profile : Kidepo LWSC \$ Approach Roads	906-01-DWG-C-PP-007A	
Option I	906-01-DWG-C-PP-008A	
LWSC \$ Approach Roads : Detail OG for Kidepo LWSC	906-01-DWG-C-PP-006.4A	
Typical Schematics Diagram for Kidepo LWSC (Option 1)	906-01-DWG-C-PP-009A	
LWSC \$ Approach Roads : Structural Sectional Details for Kidepo (Option 1)	906-01-DWG-C-PP-006.5A	
Aidepo (Option I) LWSC	906-01-DWG-C-PP-006.6A	
Plan # Longitudinal Profile : Kidepo LWSC # Approach Roads _ Option 2 (Current LWSC)	906-01-DWG-C-PP-006B	
LWSC & Approach Roads Detail 07 : Kidepo LWSC _Option 2 Current LWSC)	906-01-DWG-C-PP-006.4B	
STANDARD DRAWINGS		
LWSC # Approach Roads : Pipe Fabrications Details	906-01-DWG-C-5D-001	
LWSC \$ Approach Roads : Culvert Installation Details	906-01-DWG-C-5D-002	
LWSC \$ Approach Roads : Culvert Bedding and Backfilling Details	906-01-DWG-C-5D-003	
LWSC & Approach Roads : Standard Road Signs	906-01-DWG-C-5D-004	
LWSC & Approach Roads : Road Signs Mounting Details	906-01-DWG-C-SD-005	

CONSULTANT:

Plot 107 Kira Road, Kamwokya, P.O.Box 8493, Kampela-Uganda Tel: +256 (0)393 740800 / 0)701 740800 Email: mbw@mbw.co.ug

FUNDER:



CLIENT:



PROJECT NAME: USAID ACTIVITY NA

USAID / Uganda Architect & Engineering Design and Construction Management Services					
ACTIVITY NAME: Infrastructure for Biod	diversity Conservation in Kidepo Valley NP				
DRAWING DESCRIPTION:					
	LWSC_LIST OF DRAWING LIST OF DRAWINGS 1				

DESIGNED BY:					ENGINEER'S SEAL
DRAWN BY:					-
CHECKED BY:					-
APPROVED BY:	RFV.No.	DATE	DESCRIPTION OF REVISION	BY	

STATUS: DATE: PAPER
Construction SEP. 2022 A3 STATUS: 906-01-DWG-C-LD-001 COPYRIGHT RESERVED

GENERAL NOTES 1: IN CASE OF DISCREPANCIES BETWEEN THE GENERAL NOTES/DETAILS AND ANY NOTES/DETAILS ON INDIVIDUAL DRAWINGS, THE NOTES / DETAILS ON EACH DRAWING TAKE PRECEDENCE

1. GENERAL 2. APPROACH ROADS THE APPROACH ROADS AND THEIR COMPONENTS ARE DESIGNED ACCORDING TO THE THE STRUCTURES AND THEIR COMPONENTS ARE DESIGNED ACCORDING TO THE 2.1. CRITERIA INDICATED BY THE REGULATIONS BELOW. ALL THE REGULATIONS BELOW CRITERIA INDICATED BY THE FOLLOWING ROAD DESIGN MANUALS AND STANDARDS FROM ARE IN THE LATEST VERSIONS: MINISTRY OF WORKS AND TRANSPORT: INTERNATIONAL DESIGNS CODES. Volume 1 - 'Geometric design" EN 1990 - 'Eurocode 0: Basis of Structural design" Volume 2 - 'Drainage design manual' EN 1991 - 'Eurocode 1: Actions on Structures" Volume 3 - 'Part I: Flexible Pavement design manual " Volume 3 - 'Part II: Rigid Pavement design manual' EN 1992 - 'Eurocode 2: Design of Concrete Structures" EN 1993 - 'Eurocode 3: Design of Steel Structures" Volume 3 - 'Part I: Gravel Roads design manual" EN 1997 - 'Eurocode 7: Geotechnical design" Volume 3 - 'Part IV: Pavement Rehabilitation design manual' Volume 4 - 'Bidge design manual" EN 1998 - 'Eurocode 8: Design of structures for earthquake resistance" IN HARMONISATION OF PROFESSIONAL PRACTICE AND ENSURING APPROPRIATE LEVELS OF SAFTETY, HEALTH AND ECONOMY WITH DUE CONSIDERATION OF THE OBJECTIVES CONDITIONS AND NEED OF THE CONSTRUCTION THE STANDARD SPECIFICATION FOR BUILDING WORKS FOR MINISTRY OF WORKS HOUSING AND COMMUNICATIONS SHOULD BE APPLIED HAND IN HAND WITH THE NAMED STANDARDS. DIMENSIONS ARE NOT TO BE SCALED FROM THE DRAWINGS. FOLLOW WRITTEN 1.3. DIMENSIONS ONLY. ALL DRAWINGS SHALL BE READ IN CONJUNCTION WITH THE RELEVANT ARCHITECTURAL DRAWINGS, SPECIFICATIONS, BILLS OF QUANTITIES AND ALL OTHER RELEVANT DOCUMENTS. DISCREPANCIES MUST BE REPORTED IMMEDIATELY TO THE ENGINEER PRIOR TO COMMENCEMENT OF ANY WORK. THE CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCEMENT OF WORKS AND ANY DISCREPANCIES SHALL BE REPORTED TO THE ENGINEER BEFORE EXECUTION. ALL CONCRETE SIZES AND LEVELS ARE FOR STRUCTURAL ELEMENTS UNLESS OTHERWISE NOTED. 1.7. NO HOLES OR CHASES ARE PERMITTED IN THE CONCRETE MEMBERS OTHER THAN AS DETAILED OR UNLESS APPROVED BY THE ENGINEER. CONSTRUCTION JOINTS SHALL BE LOCATED TO THE APPROVAL OF THE ENGINEERS. ANY DAMAGE CAUSED TO ANY CIVIL/ STRUCTURAL WORK SHALL BE REINSTATED TO 1.9. ITS ORIGINAL CONDITION WITH NO COST IMPLICATION TO THE CLIENT.

CONSULTANT:





FUNDER:

CLIENT:



PROJEC	I NAME:
	USAID / Uganda Architect & Engineering De
	Management Services
ACTIVIT	Y NAME:
	Infrastructure for Biodiversity Conservation
DRAWIN	G DESCRIPTION:

nda Architect & Engineering Design and Construction Management Services	
e for Biodiversity Conservation in Kidepo Valley NP	-
IN: LWSC_LIST OF GENERAL NOTES	\neg
LIGHT OF OCHERAL MOTERS A	- 1

DESIGNED BY:					ENGINEER'S SEAL	SCALE:
DRAWN BY:						As Not
CHECKED BY:						Construct DRAWING N
APPROVED BY:						906-0
WF	REV.No.	DATE	DESCRIPTION OF REVISION	BY		COPYRIGH

tion SEP. 2022 A3

GENERAL NOTES 2: IN CASE OF DISCREPANCIES BETWEEN THE GENERAL NOTES/DETAILS AND ANY NOTES/DETAILS ON INDIVIDUAL DRAWINGS, THE NOTES / DETAILS ON EACH DRAWING TAKE PRECEDENCE

3. CONCRETE

- 3.1 UNLESS OTHERWISE SPECIFIED, ALL STRUCTURAL CONCRETE MIX TO BE OF GRADE 30
- ALL CONCRETE STRENGTHS ARE 28 DAYS CUBE STRENGTH.
- 3.3 UNLESS OTHERWISE SPECIFIED. A LAYER OF 50mm THICK GRADE 15 CONCRETE TO BE PROVIDED BELOW ALL REINFORCED CONCRETE STRUCTURES IN CONTACT WITH THE GROUND.
- UNLESS OTHERWISE SPECIFIED. ALL LEAN CONCRETE MIX TO BE OF GRADE 15.
- MAXIMUM AGGREGATE SIZE SHALL BE 20mm.
- 3.6 CURING OF CONCRETE
 - EXPOSED CONCRETE SURFACES SHOULD BE COVERED WITH DAMP ABSORBENT MATERIAL AFTER PLACING CONCRETE.
 - THEY SHOULD BE KEPT CONTINUOUSLY WET BY FREQUENT SPRAYING OF WATER.
 - IN COLUMNS CURING SHOULD BE STARTED IMMEDIATELY AFTER REMOVAL OF FORMWORK.
 - MINIMUM PERIOD OF CURING IS 4 DAYS.

3.7 REMOVAL OF SHUTTERING:

STRUCTURAL ELEMENTS	MINIMUM PERIOD
VERTICAL FORMWORK TO COLUMNS AND WALLS	24 HOURS
SOFFIT FORMWORK TO SLABS	10 DAYS
SOFFIT FORMWORK TO BEAMS	10 DAYS
PROPS TO BEAMS	14 DAYS

3.8 GRADE OF CONCRETE

CONCRETE	CUBE/ CYLINDER	CHARACTERISTIC STRENGTH, N/mm²
BLINDING SCREED / LEVELING CONCRETE	C15, (C12)	15
MASS CONCRETE	C20, (C15)	20
STRUCTURAL CONCRETE	C30, (C25)	30

4. REINFORCEMENT

- 4.1. UNLESS OTHERWISE SPECIFIED. ALL STEEL REINFORCEMENT BARS AND WELDED STEEL FABRIC REINFORCEMENTS (WSFR) SHALL COMPLY WITH THE REQUIREMENTS OF EUROCODE 2.
- 'R' DENOTES MILD STEEL OF YIELD STRENGTH = 250 N/MM2
- T' DENOTES HIGH TENSILE DEFORMED BARS (TYPE 2) OF YIELD STRENGTH = 460 N/MM2 4.3.
- CONCRETE COVER TO OUTERMOST REINFORCEMENT, INCLUDING LINKS, SHALL BE AS FOLLOWS:

STRUCTURAL ELEMENTS	IN CONTACT WITH GROUND	OTHER
SLABS	50 mm	20 mm
BEAMS	50 mm (TOP) 50 mm (SIDE & BOT.)	25 mm
COLUMNS	50 mm	40 mm
FOOTINGS	50 mm	

WELDING OF REINFORCEMENT WILL NOT BE PERMITTED WITHOUT THE APPROVAL OF THE ENGINEER.

BAR SIZE (mm)	6	10	12	16	20	25	32
T = HIGH YIELD STEEL	-	500	600	800	1000	1200	1330
R = MILD STEEL	300	-	-	-	-	-	-

ALL BARS SHALL BE CUT AND BENT TO CONFORM TO EUROCODE 2. UNLESS OTHERWISE STATED IN THE DRAWINGS, THE MINIMUM LAP LENGTH FOR REINFORCEMENT SHALL BE 50 TIMES THE DIA. OF SMALLER BAR IN THE LAP.

BAR SIZE (mm) A	В	С
T32	1100	-	900
T25	850	-	700
T20	700	-	330
T16	330	450	450
T12	400	400	400
T10	-	300	-

ALL BARS AT THE ENDS OF THE BEAMS WHERE THE BEAM IS NO MORE CONTINUOUS SHALL BE ANCHORED EITHER STRAIGHT OR BENT (DEPENDING ON THE WIDTH OF THE SUPPORT) AS SHOWN BELOW. THESE SHALL NOT BE USED IN CANTILEVERED BEAMS OR SLABS. THE ACTUAL DESIGN DRAWING SHALL BE STRICTLY ADHERE TO.

CONSULTANT:



FUNDER:



CLIENT:

	Uganda Wildlife
	Authority
	Qugandawidlifeautority
	PO Box 3530, Kampala,
	Uganda
1	Tel +256-41-355114, 355111,
•	355118

PROJECT NAME: USAID / Uganda Architect & Engineering Design and Construction ACTIVITY NAME:

Infrastructure for Biodiversity Conservation in Kidepo Valley NP DRAWING DESCRIPTION LWSC_LIST OF GENERAL NOTES

REV.No. DATE

DESIGNED BY:			ENGIN
68			
DRAWN BY:			
CHECKED BY:			
APPROVED BY:			

Construction SEP. 2022

GENERAL NOTES 3: IN CASE OF DISCREPANCIES BETWEEN THE GENERAL NOTES/DETAILS AND ANY NOTES/DETAILS ON INDIVIDUAL DRAWINGS, THE NOTES / DETAILS ON EACH DRAWING TAKE PRECEDENCE

5. NOTES ON LOW WATER STEAM CROSSINGS

IN THE CONSTRUCTION OF THE LOW WATER STREAM CROSSING, THE FOLLOWING SPECIFICATIONS SHOULD BE CONSIDERED TO OVERCOME THE PRESENT ENCUMBRANCES EXPERIENCED AT THE SITES:

- 5.1 UNDER-SCOURING/CUTTING OF THE PAVEMENT HAS BEEN PREVENTED BY INTRODUCING EDGE BEAMS ON TOP OF GABION MATTRESSES FILLED WITH STONES.
- 5.2 MINIMIZING OR AVOIDING THE DAMMING EFFECT WHICH CREATES SILTING NEAR THE DRIFT UPSTREAM HAS BEEN ACHIEVED BY ENABLING THE DRIFT'S VERTICAL ALIGNMENT TO CREATE A SELF-CLEANING EFFECT AT THE CROSSING THROUGH RIVER TRAINING.

THIS SHOULD BE DONE HAVING IN MIND THAT LWSC ARE DESIGNED FOR
OVERTOPPING WITH FLOODWATER AND CONSEQUENTLY HAVE AN INHERENT
VERTICAL DIP CHARACTERISTIC. THE APPROACH ROADWAY SHALL BE AT THE
NORMAL GROUND LEVEL ON THE STREAM BANKS, WHEREAS THE LOW POINT OF THE
CROSSING MAY BE MUCH CLOSER TO THE NORMAL WATER FLOW SURFACE THAN A
TYPICAL CULVERTED DESIGN. IT SHOULD HOWEVER BE NOTED THAT THIS SUDDEN
DIP IN THE VERTICAL ALIGNMENT IS INCONSISTENT WITH THE DRIVER'S
EXPECTATIONS OF A PUBLIC HIGHWAY PROFILE. THAT IS WHY PROPER SIGNAGE
SHOULD BE PUT IN PLACE FOR SAFETY. FOR AN EFFECTIVE SELF-CLEANING SYSTEM, IT
IS NECESSARY TO TRAIN THE RIVER INCLUDING DREDGING 100 M UPSTREAM AND
DOWNSTREAM OF THE DRIFT.

- 5.3 TO CREATE A GOOD BASE/FOUNDATION FOR THE DRIFT AND AT THE SAME TIME
 REDUCE THE VERTICAL GRADE OF THE ROAD AT THE CROSSING, IT MAY BE
 NECESSARY TO FILL THE RIVERBED WITH COMPACTED APPROVED GRAVEL AND
 HARDCORE IN LAYERS.
- 5.4 THE DRIFT SHOULD HAVE ANCHORAGE PREFERABLY AT THE RIVER BANK IN FORM OF A STABLE ROCK TO PREVENT IT FROM BEING WASHED AWAY BY THE RIVER FLOW. IN CASE A STABLE ROCK IS NOT AVAILABLE, A REINFORCED CONCRETE ANCHORAGE SHOULD BE PROPOSED.

CONSULTANT:

CONSULTING

Plot 107 Kira Road, Karmwokya, P.O.Box 8493, Karmpala-Uganda Tel: +256 (0)393 740800 / 0)701 740800 Email: mbw@mbw.co.ug FUNDER:



CLIENT:

Uganda Wild Authority Gugandawidishaut PO Bau 3530, Kamp Uganda Tel 42544-1358118


PROJECT NAME:
USAID / Uganda Architect & Engineering Design and Construction Management Services
ACTIVITY NAME: Infrastructure for Biodiversity Conservation in Kidepo Valley NP

DRAWING DESCRIPTION


Conservation in Kidepo Valley NP				
100 HOT OF OFFICE H HOTES				

DESIGNED BY:					ENGINEER'S SEAL	
DRAWN BY:			7. On 11. On 11.	_	-	SCALE: As Noted
BK						STATUS:
CHECKED BY:						Construction
BB						DRAWING NUMBER
APPROVED BY:						906-01-DW
WF	REV.No.	DATE	DESCRIPTION OF REVISION	BY		COPYRIGHT RES


LOCATION MAP



TYPICAL DRAWINGS OF LWSC AND APPROACH ROAD



LWSC	Splash apron (m)	L1 (m)	L2 (m)	L3 (m)
Kalabe	8.00	26.00	9.00	-
Kurao	1.90	18.00	7.00	_ @#~ C
Lopiripir	3.30	28.00	11.00	11.00
Nakao	1.80	32.00	4.00	-
Tongbore	6.20	10.00	5.00	20.00
Kidepo	2.60	42.00	24.00	-



SCHEMATIC DIAGRAM OF LWSC

CONSULTANT:



FUNDER:



CLIENT:

4460 m333	
	- 1
5	
IWA	
inserving for Conservions	- 1

PROJECT NAME: USAID / Uganda Architect & Engineering Design and Construction Management Services	-
ACTIVITY NAME: Infrastructure for Biodiversity Conservation in Kidepo Valley NP	\blacksquare
DRAWING DESCRIPTION:	
LWSC_RIVER APPROACH TYPICAL APPROACH ROAD SECTIONS_01	

DESIGNED BY:					ENGINEER'S SEAL
ВВ					1
DRAWN BY:					1
ВК]
CHECKED BY:]
BB					
APPROVED BY:					
WF	DEV/ No	DATE	DESCRIPTION OF REVISION	BY	

Construction SEP. 2022 A3 906-01-DWG-C-TS-001 COPYRIGHT RESERVED

